



# NORTHWEST FLORIDA BEACHES INTERNATIONAL AIRPORT

## NORTHWEST FLORIDA BEACHES INTERNATIONAL AIRPORT PANAMA CITY – BAY COUNTY AIRPORT AND INDUSTRIAL DISTRICT GENERAL FORM OF CONTRACT

**Contractor:** Rosenbauer Minnesota, LLC  
**Address:** 5181 260 Street, Wyoming, MN 55092  
**Contact:** Duane Kann  
**Telephone Number(s):** 612-910-6388  
**Email:** dkann@rosenbaueramerica.com

**Contract Title:** 1,500 Gallon ARFF Vehicle  
**Work Location:** Northwest Florida Beaches International Airport  
**Owner:** Panama City – Bay County Airport and Industrial District  
**Address:** 6300 West Bay Parkway, Suite A  
Panama City Beach, FL 32409  
**Telephone Number:** (850) 636-8950

This equipment contract (hereinafter the "Contract") is effective as of the 12<sup>th</sup> day of July, 2021 between Owner and the above named Contractor who hereby agree that all Work specified below shall be performed by the Contractor in accordance with all provisions of this Contract, consisting of the following Project Documents:

1. This General Form of Contract and duly entered written modifications issued after execution of this Contract, including but not limited to duly issued Change Notices/Orders
2. Contractor's submitted Bid Proposal, including but not limited to Exhibit "A" (proposal and pricing information), Exhibit "B" (Public Entity Crimes Statement), and Exhibit "C" (Non-Collusion Affidavit)
3. Exhibit "A" – Invitation to Bid
4. Exhibit "B" – Scope of Work and Technical Specifications
5. Exhibit "C" – Addendum # \_\_\_\_\_
6. Purchase Order – Signed Purchase Order #16863 dated 7/7/2021.

Contractor shall commence the Work within ten (10) calendar days after the Notice to Proceed is issued by the Owner, which shall be issued within ninety (30) calendar days (or such longer period of time the Owner and Contractor may mutually agree to in

writing) of the execution of this Contract, Owner shall issue a Notice to Proceed to Contractor.

The Owner's issuance of the Notice to Proceed is expressly conditioned upon the satisfaction of the following condition precedents:

1. A Project Schedule for the Work has been delivered and is acceptable to the Owner.

Owner shall determine, in its sole discretion, whether these condition precedents have been satisfied, shall be final and binding on the Contractor. Should Owner determine that all such condition precedents have not been satisfied (or otherwise waived in writing by Owner, in its sole discretion), then Owner may send Contractor written notice that Owner has elected to terminate this Contract, in which event this Contract shall automatically be terminated and neither party shall have any further liability or obligation hereunder whatsoever to the other party. In the event of any such termination prior to issuance of the Notice to Proceed, Contractor acknowledges and agrees that it shall not be entitled to and Owner shall not be liable for any payments to Contractor arising out of or relating to this Contract.

**Work to Be Performed:** Except as specified elsewhere in the contract, Contractor shall furnish all plant; labor; materials; tools; supplies; equipment; transportation; supervision; safety; technical; professional; and other services; and shall perform all operations necessary and required to satisfactorily accomplish the Work all strictly in accordance with all requirements of the Bid and Project Documents.

**Schedule:** The Work shall be performed and completed by the last quarter of calendar year 2022 unless otherwise approved by Owner.

**Compensation:** As full consideration for the satisfactory performance by Contractor of this Contract, Owner shall pay to Contractor compensation in accordance with the prices set forth in Contractor's "Bid Proposal, Exhibit A" and the payment provisions of the Project Documents.

**Payment Procedures:** The successful Bidder shall be required as a pre-requisite of the Notice to Proceed to provide the Owner a "Schedule of Values," a statement allocating portions of the Contract Price to various portions of the Work and used as the basis for reviewing "Contractor's Application for Payment." Only a Contractor's Application for Payment that corresponds directly with the "Schedule of Values" approved by the Owner or its representative will be acceptable for payment consideration.

The Contractor shall submit three (3) signed and notarized original copies of each Application of Payment (Invoice) for Work completed and/or stored to date along with waivers of lien, schedule updates and other pertinent information. The Owner's Representative will review the Application for Payment, evaluate the status of the Work

and recommend the amount to be authorized for payment less 10% retained by the Owner until the project is complete.

The amount authorized for payment will be made to the Contractor by the Owner within thirty (30) days of the date of the Application of Payment. Retained amounts shall be released to the Contractor within thirty (30) calendar days of final acceptance of the Work by the Owner or its representative.

This Contract embodies the entire agreement between Owner and Contractor and supersedes all other writings. The parties shall not be bound by or be liable for any statement, representation, promise, inducement, or understanding not set forth herein.

**OWNER**  
**Panama City – Bay County Airport**  
**& Industrial District**

**CONTRACTOR**  
**Rosenbauer Minnesota, LLC.**

By:

By:

Authorized  
Signature: 

Authorized  
Signature: 

Print Name: Parker W. McCauley Jr. Print Name: Christian Kleebauer – CEO

Panama City Bay County Airport and Industrial District  
6300 West Bay Parkway Box A  
Panama City, Florida 32409

**ORIGINAL**

# Purchase Order

MSDS Required

PO Number 16863

Telephone (850) 636-8950 Fax (850) 785-5674

Vendor Name and Address		Delivery Instructions	Tax Exempt Certificate Number
Rosenbauer Minnesota, LLC		Northwest Florida Beaches International Airport	85-8012646249C-9
5181 260th Street			
Wyoming, MN 55092			
Duane Kann (612) 910-6388		Panama City, Florida 32409	

Location or Project Code	Work Performed	Expense Account Number	Description	Quantity	Unit Price	Total
/			1,500 Gallon ARFF Vehicle per bid document dated 05/07/2021	1	\$ 689,820.00	\$ 689,820.00
/			Foam Testing System per bid document dated 05/07/2021	1	\$ 6,900.00	\$ 6,900.00
/			Additional Options	LS	\$ 20,837.00	\$ 20,837.00
/					Sub Total	\$ 717,557.00
/			Airport Board Approved 06/30/2021		S & H	
					Total	\$ 717,557.00

Amount

Vendor

No Bid	E-One
\$711,354	Oshkosh (Less Options)
\$696,720	Rosenbauer (Less Options)

Price Quotation  
Summary for  
Purchases Over  
\$500.00

\*\*\* Attach written quotation  
or bid as required \*\*\*

Requested By:	Signature	Date
Received:		
Approval:		



# **NORTHWEST FLORIDA**

## **BEACHES INTERNATIONAL AIRPORT**

### **INVITATION TO BID** **1,500 Gallon Aircraft Rescue & Firefighting (ARFF) Vehicle**

The Panama City-Bay County Airport and Industrial District dba Northwest Florida Beaches International Airport (ECP) is accepting bids for a project to provide a 1,500-gallon aircraft rescue & firefighting vehicle for the Northwest Florida Beaches International Airport.

Acceptance of a bid for the project will be contingent on successful receipt of a Federal Aviation Administration Airport Improvement Program grant by ECP for the project. Failure to secure a grant will be grounds to reject all bids.

The scope of work for the project is the manufacture and providing of a Class 4, 1,500-gallon ARFF vehicle per attached specification in accordance with Federal Aviation Administration guidelines for such acquisition. The scope also includes the providing of an input-based Aqueous Film Forming Foam (AFFF) Testing System compliant with NFPA 412, Standard for Evaluating Aircraft Rescue and Firefighting Foam Equipment. The scope of work is intended to provide a new, fully operational, vehicle to provide ARFF support at the Airport. Equipment and performance capability will meet, or exceed, requirements for an ARFF vehicle contained in:

- Federal Aviation Administration Advisory Circular #150/5220-10E, Guide Specifications for Aircraft Rescue and Fire Fighting (ARFF) Vehicles.
- National Fire Protection Association (NFPA) 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition).
- National Fire Protection Association (NFPA) 412, Standard for Evaluating Aircraft Rescue and Firefighting Foam Equipment.
- FAA Cert Alert No. 19-01.

Specific performance requirements for this scope of work are:

- Outlined in attached Procurement Specification

Bids submittal to include:

- All costs to provide a Class 4, 1,500-gallon ARFF vehicle, as outlined in the scope of work to include manufacture, freight and delivery to the Northwest Florida Beaches International Airport, acceptance testing, and operational training.
- All costs to provide an Input-based Aqueous Film Forming Foam (AFFF) Testing System compatible with provided ARFF vehicle.
- All costs to provide optional equipment per this "Invitation to Bid".
- References confirming experience where bidder has provided similar equipment to that contained within this Invitation to Bid within the past five (5) years.
- A material list that includes the manufacturer and model number of the key critical system components.
- Documentation of support items required by the Specification and this Invitation to Bid.

There is no express or implied obligation for the Panama City-Bay County Airport and Industrial District to reimburse responding firms for any expenses incurred in preparing proposals in response to this Invitation to Bid.

The Panama City-Bay County Airport and Industrial District reserves the right to reject any or all bids, to waive any irregularities or informalities in any bid or in the bid procedures, and to accept or reject any item or combination of items. ECP will be the sole judge in determining as equivalent products. The Panama City-Bay County Airport and Industrial District will select the low bidder for contract negotiations if the low bidder fully complies with the Specification. In the event that the low bidder does not fully comply with the Specification, the Panama City-Bay County Airport and Industrial District will give consideration to all deviations in the low bid and any deviations in the other bids, as well as the relative pricing of the bids, and either select the bid that provides the best value to Panama City-Bay County Airport and Industrial District or reject all bids. Any bid that substantially deviates from the Specification in the sole discretion of the Panama City-Bay County Airport and Industrial District will be deemed non-responsive.

**Please provide any questions regarding this Invitation to Bid in writing to Richard A. McConnell, Deputy Executive Director, by fax (850-785-5674) or e-mail ([accounting@pcairport.com](mailto:accounting@pcairport.com)) no later than 10 a.m. (CST) on May 5, 2021. All questions and responses will be posted to the Airport website ([www.iflvbeaches.com](http://www.iflvbeaches.com)) on Friday, May 7, 2021. It is the responsibility of the bidder to check the website for any additional information related to this bid.**

**Sealed bids must be delivered to the Administrative Offices of the Northwest Florida Beaches International Airport, 6300 West Bay Parkway, Box A, Panama City, Florida 32409 by 2 pm on May 11, 2021. Submittals should include attached Exhibits A, B and C. Please provide three (3) copies of the bid in a sealed package clearly and prominently labeled:**

**"1,500 Gallon Aircraft Rescue & Firefighting (ARFF) Vehicle – May 11, 2021"**

**Bids will be opened at 2 pm on May 11, 2021 in the Administrative Offices, upstairs in the Airport Terminal.**

## EXHIBIT A

Company Name Rosenbauer Minnesota, LLC

Address 5240 257th Street

Wyoming, MN 55092

Telephone Number 651-462-1000

Fax 651-462-9111

Contact Person Michelle Goldeman

Authorized Representative   
Signature

Christian Kleebauer  
Printed Name

CEO  
Title

## Deviations

List any deviations from the SPECIFICATIONS in this document or the attached Specification. An explanation must be provided below and documentation provided to verify compliance with the Specification and any other specifications provided by this Invitation to Bid on a similar or equivalent basis.

Item No.	Reason for deviation, description of replacement component, and/or explanation
	N/A

**Pricing Information (please print clearly)**

**Base Bid (Complete Manufacture, Delivery, Testing, Training and Warranty)**

Manufacture and Deliver a 1,500-Gallon, Class 4 ARFF Vehicle, with Input-Based Aqueous Film Forming Foam (AFFF) Testing System, as outlined in this Invitation to Bid and attached specification.

**1,500 Gallon ARFF Vehicle:** \$ 689,820.00

\$ Seven Hundred Eighty Nine Thousand Eight Hundred Twenty Dollars  
(Amount in Words)

**Input-Based Aqueous Film Forming Foam  
(AFFF) Testing System:** \$ 6,900.00

\$ Six Thousand Nine Hundred

**By signing above, authorized representative warrants to Panama City-Bay County Airport and Industrial District that the price quoted is good for 90 days after the bid date.**

**EXHIBIT B**

**SWORN STATEMENT UNDER SECTION 287.133(3)(A)**  
**FLORIDA STATUTES, ON PUBLIC ENTITY CRIMES**

THIS FORM MUST BE SIGNED AND SWORN TO IN THE PRESENCE OF A NOTARY PUBLIC OR OTHER OFFICIAL AUTHORIZED TO ADMINISTER OATHS.

1. This sworn statement is submitted to the Panama City-Bay County Airport and Industrial District

by Christian Kleebauer - CEO  
(print individual's name and title)

for Rosenbauer Minnesota, LLC  
(print name and entity submitting sworn statement)

whose business address is  
5240 257th Street  
Wyoming, MN 55092

and (if applicable) its Federal Employer Identification Number (FEIN) is

[REDACTED]

(if the entity has no FEIN, include the Social Security No. of the individual signing this sworn statement:

N/A.)

2. I understand that a "public entity crime" as defined in Section 287.133(1)(g) of the Florida Statutes, means a violation of any state or federal law by a person with respect to and directly related to the transaction of business with any public entity or with an agency or political subdivision of any other state or of the United States, including, but not limited to, any bid or contract for goods or services to be provided to any public entity or an agency or political subdivision of any other state or of the United States and involving antitrust, fraud, theft, bribery, collusion, racketeering, conspiracy or material misrepresentation.

3. I understand that "convicted" or "conviction" as defined in Paragraph 287.133(1)(b), Florida Statutes, means a finding of guilt or a conviction of a public entity crime, with or without an adjudication of guilt, in any federal or state trial court of record relating to charges brought by indictment or information after July 1, 1989, as a result of a jury verdict, non-jury trial or entry of a plea of guilty or *nolo contendere*.
4. I understand that "affiliate" as defined in Paragraph 287.133(1)(a), Florida Statutes, means

A. A predecessor or successor of a person convicted of a public entity crime;  
or

B. An entity under the control of any natural person who is active in the management of the entity and who has been convicted of a public entity crime. The term "affiliate" includes those officers, directors, executives, partners, shareholders, employees, members and agents who are active in the management of an affiliate. The ownership by one person of shares constituting a controlling interest in another person, or a pooling of equipment or income among persons when not for fair market value under an arm's length agreement, shall be a prima facie case that one person controls another person. A person who knowingly enters into a joint venture with a person who has been convicted of a public entity crime in Florida during the preceding 36 months shall be considered an affiliate.

5. I understand that a "person" as defined in Paragraph 287.133(1)(e), Florida Statutes, means any natural person or entity organized under the laws of any state or of the United States with the legal power to enter into a binding contract and which bids or applies to bid on contracts for the provision of goods or services let by a public entity, or which otherwise transacts or applies to transact business with a public entity. The term "person" includes those officers, directors, executives, partners, shareholders, and employees, members, and agents who are active in management of an entity.
6. Based on information and belief, the statement which I have marked below is true in relation to the entity submitting this sworn statement. (Indicate which statement applies.)

  X   Neither the entity submitting this sworn statement, nor any of its officers, directors, executives, partners, shareholders, employees, members, or agents who are active in the management of the entity, nor any affiliate of the entity has been charged with and convicted of a public entity crime subsequent to July 1, 1989.

       The entity submitting this sworn statement, or one or more of its officers, directors, executives, partners, shareholders, employees, members, or agents who are active in the management of the entity, or an affiliate of the entity has been charged with and convicted of a public entity crime subsequent to July 1, 1989.

\_\_\_\_\_ The entity submitting this sworn statement, or one or more of its officers, directors, executives, partners, shareholders, employees, members, or agents who are active in the management of the entity, or an affiliate of the entity has been charged with and convicted of a public entity crime subsequent to July 1, 1989. However, there has been a subsequent proceeding before a Hearing Officer of the State of Florida, Division of Administrative Hearings and the Final Order entered by the Hearing Officer determined that it was not in the public interest to place the submitting this sworn statement on the convicted vendor list. (Attach a copy of the final order.)

**I UNDERSTAND THAT THE SUBMISSION OF THIS FORM TO THE CONTRACTING OFFICER FOR THE PUBLIC ENTITY IDENTIFIED IN PARAGRAPH 1 (ONE) ABOVE IS FOR THAT PUBLIC ENTITY ONLY AND THAT THIS FORM IS VALID THROUGH DECEMBER 31 OF THE CALENDAR YEAR IN WHICH IT IS FILED. I ALSO UNDERSTAND THAT I AM REQUIRED TO INFORM THE PUBLIC ENTITY PRIOR TO ENTERING INTO A CONTRACT IN EXCESS OF THE THRESHOLD AMOUNT PROVIDED IN SECTION 287.107, FLORIDA STATUTES FOR CATEGORY TWO OF ANY CHANGE IN THE INFORMATION CONTAINED IN THIS FORM.**

  
(signature)

5/7/2021

(date)

STATE OF Minnesota

COUNTY OF Anoka

Personally appeared before me, the undersigned authority, (name of individual signing) Christian Kleebauer - CEO

who, after first being sworn by me, affixed his/her signature in the space provided above on this

7 day of May, 2021.

Subscribed and sworn to before me this 7 day of May, 2021.

My commission expires:

1/31/2022

  
Notary Public Michelle Goldman



**EXHIBIT C**

**NON-COLLUSION AFFIDAVIT**

State of Minnesota

County of Anoka

The undersigned Bidder or agent, being duly sworn, on oath says that he/she has not, nor has any other member, representative, or agent of the firm, company, corporation, or partnership represented by him/her, entered into any combination, collusion or agreement with any person relative to the price to be proposed by anyone at such letting, nor to prevent any person from submitting a bid, and that this bid is made without reference to any other bid and without any agreement, understanding or combination with any other person in reference to such proposals in any way or manner whatever.

  
\_\_\_\_\_  
Christian Kleebauer \_\_ CEO

PROPOSER OR AGENT

For Rosenbauer Minnesota, LLC  
\_\_\_\_\_  
FIRM OR CORPORATION

Subscribed and sworn to before me this 7 day of May, 2021.

My Commission Expires:

  
\_\_\_\_\_

1/31/2022

Michelle Goldeman - Notary



*Form must be signed and notarized –*

**PROCUREMENT SPECIFICATION**  
**Class 4**  
**AIRCRAFT RESCUE AND FIRE FIGHTING (ARFF) VEHICLE**

1. SCOPE. This Procurement Specification (PS) covers a commercially produced diesel engine driven ARFF vehicle for an **Index C** airport. It includes a 1500-gallon water/Aqueous Film Forming Foam (AFFF) fire suppression system: **with 450 lbs potassium-based dry chemical only complementary system.**

The ARFF vehicle is intended to carry rescue and firefighting equipment for the purpose of rescuing aircraft passengers, preventing aircraft fire loss, and combating fires in aircraft.

2. CLASSIFICATION. The ARFF vehicle(s) covered by the PS are classified in accordance with Part 139. Certification and Operations: Land Airports Serving Certain Air Carriers, Section 317, Aircraft Rescue and Firefighting: Equipment and Agents; and Federal Aviation Administration (FAA) Advisory Circular (AC) 150-52210-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles, as follows:

Airport Index	Vehicle Class	Minimum Rated Capacities (gallons/liters)
<b>Index C</b>	<b>4</b>	1500 gallons (5678 liter) water/AFFF solution

3. VEHICLE CONFORMANCE/PERFORMANCE CHARACTERISTICS. The ARFF vehicle will be in accordance with the applicable requirements of National Fire Protection Association (NFPA) 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), and AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. The manufacturer will allow the addition of other options, at the buyer's expense, after bid acceptance.

3.1 General Administration Requirements.

- 3.1.1 Manuals: Technical manuals will consist of operator, service, and parts manuals. All manuals are required to be provided in hardcopy and in digital format on CDs when requested.

- 3.1.1.1 Technical manuals. The overall format for the manuals will be commercial. Each technical manual will have a title page. Line art will be used to the maximum extent possible for illustrations and parts lists. One complete set of engine and transmission parts, service and operator's manual will be packed with each vehicle.

- a. The contractor will provide digitized manuals in CD format when requested in addition to or in place of printed paper copies.

**CLASS 4**

- b. The contractor will provide two complete sets of hardcopy manuals and / or CDs when requested.

3.1.1.1.1 Operator's manual. The operator's manual will include all information required for the safe and efficient operation of the vehicle including, fire extinguishing systems, equipment, and any special attachments or auxiliary support equipment. As a minimum, the operator's manual will include the following:

- a. The location and function of all controls and instruments will be illustrated and functionally described.
- b. Safety information that is consistent with the safety standards established by the Occupational Safety and Health Administration (OSHA) and NFPA.
- c. All operational and inspection checks and adjustments in preparation for placing the vehicle into service upon receipt from the manufacturer.
- d. Tie down procedures for transport on a low-boy trailer.
- e. Warranty information and the period of the warranty coverage for the complete vehicle and for any component warranty that exceeds the warranty of the complete vehicle. Addresses and telephone numbers will be provided for all warranty providers.
- f. General description and necessary step-by-step instructions for the operation of the vehicle and its fire extinguishing system(s) and auxiliary equipment.
- g. A description of the post-operational procedures (draining, flushing, re-servicing, et cetra).
- h. Daily maintenance inspection checklists that the operator is expected to perform, including basic troubleshooting procedures.
- i. Disabled vehicle towing procedures.
- j. Procedures and equipment required for changing a tire.
- k. Schedules (hours, miles, time periods) for required preventative maintenance and required periodic maintenance.
- l. Line art drawing of the vehicle, including panoramic views (front, rear, left, and right sides) showing basic dimensions and weights (total vehicle and individual axle weight for the unloaded and fully loaded vehicle). For the purposes of this AC, "unloaded" is defined as a lack of agent, occupants and compartment load, and "loaded" is defined as including agent, occupants and compartment load.

3.1.1.1.2 Service manual. The service manual will identify all special tools and test equipment required to perform servicing, inspection, and testing. The manual will cover troubleshooting and maintenance as well as minor and major repair procedures. The text will contain performance specifications, tolerances, and fluid capacities; current, voltage, and resistance data; test procedures; and illustrations and exploded views as may be required to permit proper maintenance by qualified vehicle mechanics. The

#### **CLASS 4**

manual will contain an alphabetical subject index as well as a table of contents. The service manual will contain at least the following, where applicable:

- a. Firefighting system schematic(s).
- b. Hydraulic schematic.
- c. Pneumatic schematic.
- d. Electrical schematic.
- e. Winterization schematic.
- f. Fuel schematic.
- g. Schedules for required preventative maintenance and required periodic maintenance.
- h. Lubrication locations, procedures, and intervals for parts of the vehicle and equipment that require lubrication.

3.1.1.1.3 Parts identification manual. The parts manual will include illustrations or exploded views (as needed) to identify properly all parts, assemblies, subassemblies, and special equipment. All components of assemblies shown in illustrations or exploded views will be identified by reference numbers that correspond to the reference numbers in the parts lists. All purchased parts will be cross-referenced with the original equipment manufacturers (OEM) name and part number. The parts identification manual will provide the description and quantity of each item used for each vehicle. The size, thread dimensions, torque specifications, and special characteristics will be provided for all nonstandard nuts, bolts, screws, washers, grease fittings, and similar items. The manual will contain a numerical index. The parts manual will contain a list of all of the component vendor names, addresses, and telephone numbers referenced in the parts list.

### 3.1.2 Painting, plating, and corrosion control.

3.1.2.1 Finish. Exterior surfaces will be prepared, primed, and painted in accordance with all of the paint manufacturer's instructions and recommendations. Vehicles will be painted and marked in accordance with AC 150/5210-5, Painting, Marking, and Lighting of Vehicles Used on an Airport. The interior finish of all compartments will be based on the manufacturer's standard production practice. This may include painting, texturing, coating or machine swirling as determined by the manufacturer. All bright metal and anodized parts, such as mirrors, horns, light bezels, tread plates, and roll-up compartment doors, will not be painted. All other surfaces capable of being painted must be in the appropriate yellow-green color.

3.1.2.2 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, Dissimilar Metals, will not be in contact with each other. Metal plating or metal spraying of dissimilar base metals to provide electromotively compatible abutting surfaces is acceptable. The use of dissimilar metals separated by suitable insulating material is permitted, except in systems where bridging of insulation materials by an electrically conductive fluid can occur.

3.1.2.3 Protection against deterioration. Materials that deteriorate when exposed to sunlight, weather, or operational conditions normally encountered during service will not be used or will have a means of protection against such deterioration that does not prevent compliance with performance requirements. Protective coatings that chip, crack, or scale with age or extremes of climatic conditions or when exposed to heat will not be used.

3.1.2.4 Reflective stripes. A minimum eight (8) inch horizontal band of high gloss red paint or red reflective tape (Retroreflective, ASTM-D 4956-09, *Standard Specification for Retroreflective Sheeting for Traffic Control*, TYPE III & above) must be applied around the vehicle's surface.

3.1.2.5 Lettering. The manufacturer will apply the airport's 'Name' and 'Insignia' (**to be provided**) in a contrasting color or by decal on both sides of the vehicle in long radius elliptical arches above and below the lettering center line. The size of the lettering will be a minimum of 2 ½-inches to a maximum of 6-inches. Reflective lettering is allowed if the material is the same as that which is used for the reflective stripe (as specified in AC 150/5210-5).

3.1.3 Vehicle identification plate. A permanently marked identification plate will be securely mounted at the driver's compartment. The identification plate will contain the following information:

- a. NOMENCLATURE
- b. MANUFACTURER'S MAKE AND MODEL
- c. MANUFACTURER'S SERIAL NUMBER
- d. VEHICLE CURB WEIGHT: kg (pounds)
- e. PAYLOAD, MAXIMUM: kg (pounds)
- f. GROSS VEHICLE WEIGHT (GVW): kg (pounds)
- g. FUEL CAPACITY AND TYPE: gals (gallons)
- h. DATE OF DELIVERY: (month and year)
- i. WARRANTY (month and km (miles))
- j. CONTRACT NUMBER
- k. PAINT COLOR AND NUMBER

A second permanently marked information data plate will be securely mounted on the interior of the driver's compartment. The plate contains the information required by NFPA 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), Section 1.3.5 Vehicle Information Data Plate. A single plate that combines or contains the information required for both plates is acceptable.

3.1.4 Environmental conditions.

3.1.4.1 Vehicle operation and storage temperature conditions will vary with geographical location. Thus, the locality temperature range can go from -40° to 110° F. Refer to NFPA 414 for vehicle winterization criteria.

## **CLASS 4**

3.1.4.2 **Temperature range.** The vehicle will be capable of satisfactory storage and operation in temperatures ranging from 33° to 110°F. The vehicle will be equipped with a cab, chassis, and agent winterization system, permitting operation at 33°F. The winterization system will not detract from the performance of the vehicle or the firefighting system in ambient temperatures up to 110°F.

3.1.5 **Reduction of potential foreign object damage.** All loose metal parts, such as pins, will be securely attached to the vehicle with wire ropes or chains. Removable exterior access panels, if provided, will be attached with captive fasteners.

3.1.6 **Vehicle Mobility.**

3.1.6.1 **Operating terrain.** The vehicle will be capable of operating safely on paved roads, graded gravel roads, cross country terrain, and sandy soil environments. Cross country terrain consists of open fields, broken ground, and uneven terrain. An off-road, high-mobility suspension system resulting in no more than 0.5 G rms acceleration at the driver's seat of the vehicle when traversing an 8-inch (20 cm) diameter half round at 35 mph (56 kph) must be provided. The suspension design by which the manufacturer meets the suspension performance requirements is at the manufacturer's discretion.

3.1.6.2 **Gradeability.** The fully loaded vehicle will be able to ascend any paved slope up to and including 50-percent.

3.1.6.3 **Side slope stability.** The fully loaded vehicle will be stable on a 30° side slope when tested in accordance with NFPA 414.

3.1.6.4 **Cornering stability.** The fully loaded vehicle will be stable in accordance with NFPA 414 when tested in accordance with NFPA 414.

3.2 **Weights and dimensions.**

3.2.1 **Overall dimensions.** The maximum dimensions listed below are desirable to ensure vehicles can be accommodated in existing fire stations. Likewise, the overall dimensions should be held to a minimum that is consistent with the best operational performance of the vehicle and the design concepts needed to achieve this performance and to provide maximum maneuverability in accordance with NFPA 414.

<b>Vehicle Capacity /Dimensions</b>	<b>1500 Gallon</b>
Length (inches/cm)	433/1100
Width (inches/cm, excluding mirrors)	124/315
Height (inches/cm)	154/391

**NOTE:** For Airport Operator Validation: Consult AC 150/5210-15, Aircraft Rescue and Fire Fighting Station Building Design, Appendix A, to ensure vehicles measurements do not exceed existing airport fire station dimensions.

**Vehicle Measurement Validation**

The facility dimensions are more than adequate to accommodate the vehicle. The entry doors are 16' x 16'.

**ADO/FAA Approval:** → \_\_\_\_\_

3.2.2 Angles of approach and departure. The fully loaded vehicle will have angles of approach and departure of not less than 30°.

3.2.3 Field of vision. The vehicle will have a field of vision in accordance with NFPA 414.

3.2.3.1 Mirrors. Combination flat and convex outside rearview mirrors will be installed on each side of the cab. The flat mirrors will be of the motorized remote-control type, providing not less than 60° horizontal rotational viewing range. The flat mirrors will also have electrically heated heads. Mirror remote and heating controls will be located on the instrument panel within reach of the seated driver. To provide the driver a clear view of the area ahead of the vehicle and to eliminate potential blind spots, a rectangular mirror will be installed on the lower corner of each side of the windshield, having a minimum area of 35 square inches.

The vehicle will have a back-up (rear-view) camera with a display monitor mounted above the driver in the cab. Cameras and monitors that are designed to replace the function of the side-view mirrors are not an approved option in this specification.

3.3 Chassis and vehicle components.

3.3.1 Engine. The vehicle will have a turbocharged diesel engine that is certified to comply with the Environmental Protection Agency (EPA) and state laws for off-highway emission requirements at the time of manufacture. The engine and transmission must operate efficiently and without detrimental effect to any drive train components and when lubricated with standard, commercially available lubricants according to the recommendations of the engine and transmission manufacturers.

3.3.1.1 Acceleration. The fully loaded vehicle will accelerate from 0 to 50 miles per hour (mph) on a level paved road within: 25 seconds.

3.3.1.2 Maximum speed. The fully loaded vehicle will attain a minimum top speed of 70 mph on a level paved road.

3.3.1.3 Pump and roll on a 40-percent grade. The fully loaded vehicle will be capable of pump and roll operations on a paved, dry, 40-percent grade in accordance with NFPA 414.

3.3.1.4 Altitude. Where justified, the vehicle, including the pumping system, will be designed for operation at 2,000 feet above sea level.

**CLASS 4**

### Justification

Altitude in Panama City, Florida is 26' above sea level.

**ADO/FAA Approval:** → \_\_\_\_\_

3.3.2 Engine cooling system. The engine cooling system will be in accordance with NFPA 414. A label will be installed near the engine coolant reservoir reading “Engine Coolant Fill”.

**3.3.3 Fuel system.** The fuel system will be in accordance with NFPA 414.

3.3.3.1 Fuel priming pump. The vehicle will be equipped with an electric or pneumatic fuel pump in addition to the mechanical fuel pump. The electric/pneumatic pump will be used as a priming pump capable of re-priming the engines fuel system.

3.3.3.2 Fuel tank. The vehicle will have one or two fuel tanks with a minimum usable capacity in accordance with NFPA 414, as amended by NFPA 414. Each tank will have a fill opening of 3 inches minimum, readily accessible to personnel standing on the ground and designed to prevent fuel splash while refueling. Each tank will be located and mounted so as to provide maximum protection from damage, exhaust heat, and ground fire. If more than one tank is furnished, means will be provided to assure equalized fuel level in both tanks. An overturn fuel valve will be provided for each tank to prevent spillage in the event of a rollover. Each fuel tank must be prominently labeled "Diesel Fuel Only".

3.3.4 Exhaust system. The exhaust system will be in accordance with NFPA 414. The exhaust system will be constructed of high-grade rust resistant materials and protected from damage resulting from travel over rough terrain. The muffler(s) will be constructed of aluminized steel or stainless steel. Exhaust system outlet(s) will be directed upward or to the rear, away from personnel accessing equipment compartments and the engine air intake, and will not be directed toward the ground.

3.3.5 Transmission. A fully automatic transmission will be provided. The transmission will be in accordance with NFPA 414.

3.3.6 Driveline. The vehicle driveline will be in accordance with NFPA 414. If the driveline is equipped with a differential locking control, a warning/caution label will be placed in view of the driver indicating the proper differential locking/un-locking procedures. The operator's manual will also include a similar warning/caution. All moving parts requiring routine lubrication must have a means of providing for such lubrication. There must be no pressure lubrication fittings where their normal use would damage grease seals or other parts.

3.3.7 Axle capacity. Each axle will have a rated capacity, as established by the axle manufacturer, in accordance with NFPA 414.

3.3.8 Suspension. The suspension system will be in accordance with NFPA 414 and AC 150/5220-10, Guide Specification for Aircraft Rescue Fire Fighting (ARFF) Vehicles.

## CLASS 4

3.3.9 Tires and wheels. Tires and wheels will be in accordance with NFPA 414. The vehicle will be equipped with single tires and wheels at all wheel positions. The vehicle will be equipped with tubeless steel belted radial tires with non-directional on/off-road type tread mounted on disc wheel assemblies. Tire and wheel assemblies will be identical at all positions. Tires and wheels will be certified by the manufacturer for not less than 25 miles of continuous operation at 60 mph at the normal operational inflation pressure. A spare tire and wheel assembly will be provided; however, the spare tire and wheel assembly are not required to be mounted on the vehicle. Tires will be new. Retreads, recaps, or re-grooved tires will not be permitted.

Tire bead locks, where justified, may be installed on all tires and rims.

Justification
Not Applicable.
ADO/FAA Approval: → _____

3.3.10 Towing connections. The vehicle will be equipped with towing connections in accordance with NFPA 414. The vehicle will be designed for flat towing; the capability to lift and tow the vehicle is not required. The tow connections may intrude into the 30-degree approach angle.

3.3.11 Brake system. The vehicle will be equipped with a multi-channel all-wheel antilock brake system with at least one channel for each axle. The brakes will be automatic; self-adjusting and fully air-actuated. Brakes will be in accordance with CFR 49 CFR 393.40 through 393.42(b), 393.43, and 393.43 through 393.52. The braking system, complete with all necessary components will include:

- a. Air compressor having a capacity of not less than 16 standard cubic feet per minute (SCFM).
- b. Air storage reservoir(s), each tank equipped with drain (bleed) valves, and with safety and check valves between the compressor and the reservoir tank.
- c. Automatic moisture ejector on each air storage reservoir. Manual air tank drains are acceptable if they are labeled, are centrally located in one compartment and are accessible by an individual standing at the side of the vehicle.
- d. Automatic slack adjusters on cam brakes or internal self-adjusting brakes on wedge brakes on all axles.
- e. Spring set parking brakes.

All components of the braking system will be installed in such a manner as to provide adequate road clearance when traveling over uneven or rough terrain, including objects liable to strike and cause damage to the brake system components. No part of the braking system will extend below the bottom

of wheel rims, to ensure, in case of a flat tire, that the weight of the vehicle will be supported by the rim and the flat tire and not be imposed on any component of the braking system. Slack adjusters and air chambers will be located above the bottom edge of the axle carrier.

3.3.11.1 Air dryer. A replaceable cartridge desiccant air dryer will be installed in the air brake system. The dryer will have the capability of removing not less than 95 percent of the moisture in the air being dried. The dryer will have a filter to screen out oil and solid contaminants. The dryer will have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve.

3.3.11.2 Compressed air shoreline or vehicle-mounted auxiliary air compressor. A flush mounted, check valve, auto-eject compressed air shoreline connection will be provided to maintain brake system pressure while the vehicle is not running. The shoreline will be flush mounted (not to extend outside the body line), located on the exterior of the vehicle, either on the left side rear corner of the cab, or at the rear of the vehicle. In lieu of a compressed air shoreline connection, the vehicle may be equipped with a 110-volt shoreline connected vehicle-mounted auxiliary air compressor. In lieu of a compressed air shoreline connection, the vehicle may be equipped with an electrical shoreline connected vehicle mounted auxiliary air compressor.

3.3.12 Steering. The vehicle will be equipped with power steering. Rear-wheel steering technology is not an approved vehicle option.

3.3.12.1 Steering effort. The steering system performance will be in accordance with NFPA 414.

3.3.12.2 Turning diameter. The fully loaded vehicle will have a wall to wall turning diameter of less than three times the overall length of the vehicle in both directions in accordance with NFPA 414.

3.3.13 License plate bracket. A lighted license plate bracket will be provided at the left rear and left front of the vehicle. The location of the left front bracket will be placed so as not to interfere with the operation of firefighting systems.

3.4 Cab. The vehicle will have a fully enclosed two door cab of materials which are corrosion resistant, such as aluminum, stainless steel, or glass reinforced polyester construction. Steps and handrails will be provided for all crew doors, and at least one grab handle will be provided for each crew member, located inside the cab for use while the vehicle is in motion. The lowermost step(s) will be no more than 22 inches above level ground when the vehicle is fully loaded. A tilt and telescoping steering column will be provided.

3.4.1 Windshield and windows. The windshield and windows will be of tinted safety glass. Each door window will be capable of being opened far enough to facilitate emergency occupant escape in the event of a vehicle accident. The vehicle window will have an **electric** control system.

3.4.2 Cab interior sound level. The maximum cab interior sound level will be in accordance with NFPA 414.

3.4.3 Instruments and controls. All instruments and controls will be illuminated and designed to prevent or produce windshield glare. Gauges will be provided for oil pressure, coolant temperature, and automatic transmission temperature. In addition to the instruments and controls required by NFPA 414, the following will be provided within convenient reach of the seated driver:

#### **CLASS 4**

- a. Master warning light control switch,
- b. Work light switch(es), and
- c. Compartment "Door Open" warning light and intermittent alarm that sounds when a compartment door is open and the parking brakes are released or the transmission is in any position other than neutral.

3.4.4 Windshield deluge system. The vehicle will be equipped with a powered windshield deluge system. The deluge system will be supplied from the agent water tank and will have an independent pumping system. The deluge system activation switch will be located within reach of the seated driver and turret operator.

3.4.5 Forward Looking Infrared (FLIR). A forward looking infrared (FLIR) camera and in-cab monitor, meeting the requirements of NFPA 414, will be provided. In addition, the FLIR monitor described in NFPA 414 will have a minimum dimension of 10 in (25 cm) (measured diagonally) and be located in a position where it is visible to both the seated driver and turret operator.

3.4.6 Climate control system. The offeror/contractor's standard heater/defroster and air conditioning system will be provided. The climate control system will induct at least 60 cubic feet per minute of fresh air into the cab. Cab mounted components will be protected from inadvertent damage by personnel.

3.4.7 Seats. The driver seat will be adjustable fore and aft and for height. The turret operator's seat, located to the right front of the driver's seat, will be a fixed (non-suspension) type. Each seat will be provided with a Type 3 seat belt assembly (i.e., 3-point retractable restraint) in accordance with CFR 49 CFR 571.209. Seat belts must be of sufficient length to accommodate crew members in full Personal Protective Equipment (PPE).

3.4.7.1 Seat options. Two types of seat options are allowed in the vehicle. A standard seat contains a hard/fixed back. For these seats, a remote-mounted bracket designed to store a Self-Contained Breathing Apparatus (SCBA) will be provided. The remote-mounted bracket for the driver and turret operator (at a minimum) must be placed outside the cab if necessary. An SCBA seat, on the other hand, contains an opening which can accommodate someone wearing an SCBA. The chart below represents the user's stated preference for the vehicle seating configuration.

Position	Standard	SCBA-Seat	N/A
Driver	X		
Turret		X	
#3		X	
#4		X	

**JUSTIFICATION**

The extra seats are needed to transport additional employees during new employee training. Also, the seats will assist in transporting aircraft occupants off of the airfield after the scene is made safe.

ADO/FAA Approval: ➔ \_\_\_\_\_

3.4.8 Windshield wipers and washer. The vehicle will be equipped with electrically powered windshield wipers. The wiper arms and blades will be of sufficient length to clear the windshield area described by SAE J198, Windshield Wiper Systems – Trucks. Individual wiper controls will include a minimum of two speed settings and an intermittent setting. The wiper blades will automatically return to a park position, out of the line of vision. The vehicle will be equipped with a powered windshield washer system, including an electric fluid pump, a minimum one-gallon fluid container, washer nozzles mounted to the wiper arms (wet arms), and a momentary switch.

3.4.9 Warning signs. Signs that state “Occupants must be seated and wearing a seat belt when apparatus is in motion” will be provided in locations that are visible from each seated position in accordance with NFPA 414.

3.4.10 Lateral accelerometer and/or stability control system. The vehicle will be equipped with a lateral accelerometer and/or an electronic stability control system in accordance with NFPA 414.

3.4.11 Monitoring and Data Acquisition System (MADAS). The vehicle will be equipped with a MADAS as prescribed by NFPA 414.

3.5 Body, compartments, and equipment mounting.

3.5.1 Body. The vehicle will have a corrosion-resistant body.

3.5.2 Compartments. The vehicle body will have lighted compartments in accordance with NFPA 414 with a minimum of 10 cubic feet of enclosed storage space.

3.5.2.1 Compartment doors. Storage compartments will have clear anodized aluminum, counterbalanced, non-locking, roll-up or single hinged doors as determined by the manufacturer. Door latch handles on roll-up doors will be full-width bar type. Door straps will be provided to assist in closing the compartment doors when the rolled up or hinged door height exceeds six feet above the ground.

3.5.2.2 Scuffplates. Replaceable scuffplates will be provided at each compartment threshold to prevent body damage from sliding equipment in and out of the compartments. The scuffplates will be securely attached to the compartment threshold but will be easily replaceable in the event of damage.

3.5.2.3 Drip rails. Drip rails will be provided over each compartment door.

3.5.2.4 Shelves. An adjustable and removable compartment shelf will be provided for every 18 inches of each vertical storage compartment door opening. Shelving adjustments will require no more

**CLASS 4**

than common hand tools, and will not require disassembly of fasteners. Shelves will support a minimum of 200 pounds without permanent deformation. Each shelf will be accessible to crew members standing on the ground or using a pull out and tip-down configuration. Each shelf will have drain holes located so as to allow for drainage of any water from the stowed equipment.

3.5.2.5 Drainage mats. Each compartment floor and shelf will be covered with a removable black mat designed to allow for drainage of any water from the stowed equipment.

3.5.3 SCBA storage tubes. A single compartment or tubes for storage of four SCBA bottles will be provided. If tubes are provided, two will be installed on each side of the vehicle. The tubes will be of sufficient size to accommodate the procuring agencies SCBA cylinders.

3.5.4 Ladder, handrails, and walkways. Ladder, stepping, standing, and walking surfaces will be in accordance with NFPA 414. Handrails will be provided in accordance with NFPA 414. The lowermost step(s) or ladder rungs will be no more than 22 inches (56 cm) above level ground when the vehicle is fully loaded. The lowermost steps may extend below the angle of approach or departure or ground clearance limits if they are designed to swing clear. The tread of the bottom steps must be at least 8 inches (20 cm) in width and succeeding steps at least 16 inches (40 cm) in width. The full width of all steps must have at least 6 inches (15 cm) of unobstructed tow room or depth when measured from, and perpendicular to, the front edge of the weight-bearing surface of the step.

3.5.5 Ancillary equipment. Ancillary equipment listed in NFPA 414 A.4.2.1 (1)-(17) is not covered by the Procurement Specification in accordance with AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. Ancillary equipment is funded separately by other sources.

**NOTE:** Equipment funding will be obtained as a separate contact under the provisions of AC 150/5210-14. Aircraft Rescue and Fire Fighting Equipment, Tools, and Clothing.

3.6 Agent system.

3.6.1 Agent (fire) pump. The vehicle will be equipped with a centrifugal pump capable of providing the performance specified herein as prescribed by NFPA 414.

3.6.1.1 Agent system piping. All piping, couplings, and valves and associated components that come into contact with the agent will be in accordance with NFPA 414.

3.6.1.2 Tank to pump connection. A check valve and shutoff valve will be provided in each tank to pump line.

3.6.1.3 Piping, couplings, and valves. All agent system piping will conform to NFPA 414 criteria.

3.6.1.4 Overheat protection. The agent system will be equipped with an overheat protection system in accordance with NFPA 414. Overheat protection is not required on vehicles utilizing a pre-mixed pressurized foam system.

3.6.1.5 Pressure relief valves. The agent system will be equipped with pressure relief valves in accordance with NFPA 414.

#### CLASS 4

3.6.1.6 Drains. The agent system will be equipped with a drainage system in accordance with NFPA 414.

3.6.2 Water tank. The vehicle will have a water tank with a manufacturer certified minimum capacity of at least 1500 gallons.

3.6.2.1 Water tank construction. The water tank will be constructed of passivated stainless steel, polypropylene, or Glass Reinforced Polyester (GRP) construction. All materials used will be capable of storing water, foam concentrate, and water/AFFF solutions.

3.6.2.2 Water tank overhead fill cover and drain. The water tank will be equipped with a 20-inch fill tower. The tower will be designed to allow for video inspection of the water tank interior. The water tank will incorporate a drainage system in accordance with NFPA 414.

3.6.2.3 Water tank overflow system and venting. The water tank will incorporate a venting system to relieve pressure on the tank during fill and discharge operations at maximum flow rates. It will have an overflow system to relieve excess fluid in the event of tank overflow. Drainage from the vent and overflow system will not flow over body panels or other vehicle components and will not be in the track of any of the tires. Tank vent hoses will be of the non-collapsible type.

3.6.2.4 Water tank top fill opening. A top fill opening of not less than 8 inches internal diameter with a readily removable ¼ inch mesh strainer will be provided. The fill opening may be incorporated as part of the manhole cover, and will be sized to accommodate a 2 ½ inch fill hose.

3.6.2.5 Water tank fill connection. The water tank will incorporate National Hose thread connections and will be in accordance with NFPA 414. If the vehicle is fitted with the "structural firefighting capability option," the additional requirements listed in paragraph 3.6.8 must be incorporated.

3.6.3 Foam system. (NOTE: the requirements of section 3.6.3 do not apply to pre-mixed pressurized foam systems.)

3.6.3.1 Foam concentrate tank. The foam concentrate tank(s) will have a manufacturer certified working capacity sufficient for two tanks of water at the maximum tolerance specified in NFPA 412, Standard for Evaluating Aircraft Rescue and Fire-Fighting Foam Equipment for 3 to 6 percent foam concentrate (i.e., 7.0 percent).

3.6.3.1.1 Foam tank construction. The foam tank will be constructed of passivated stainless steel, polypropylene, or GRP construction. All materials used will be capable of storing foam concentrate.

3.6.3.1.2 Foam tank drain. The foam tank will incorporate a drain and drain valve. The valve will be on the left side of the vehicle and controlled by a crew member standing on the ground. The drain line will have a minimum 1 ½ inch I.D. The foam tank drain outlet will be located so that the contents of the tank can be drained into 5-gallon cans and 55-gallon drums.

3.6.3.1.3 Foam tank top fill trough. The foam tank will incorporate a top fill trough mounted in the top of the tank readily accessible to at least two crew members on top of the vehicle. The top fill trough will incorporate a cover, latch, and be sealed so as to prevent spillage under any operating condition. The top fill trough will be designed to allow two standard 5-gallon foam concentrate

containers to be emptied simultaneously. The top fill trough neck will extend sufficiently close to the bottom of the tank to reduce foaming to a minimum during the fill operation. The top fill trough will incorporate readily removable, rigidly constructed 10 mesh stainless steel, brass, or polyethylene strainers. All components in and around the top fill trough will be constructed of materials that resist all forms of deterioration that could be caused by the foam concentrate or water.

3.6.3.2 Foam tank fill connections. The foam tank will incorporate a 1.5 inch National Hose thread female hose connection on **both sides** of the vehicle to permit filling by an external transfer hose at flow rates up to 25-gpm. The connections will be provided with chained-on long handled plugs or rocker lug plugs. The top of the connections will be no higher than 48 inches above the ground and readily accessible. The fill lines will incorporate check valves and readily removable, rigidly constructed ¼ inch mesh strainers. All components in the foam tank fill system will be constructed of materials that resist all forms of deterioration that could be caused by the foam concentrate or water.

3.6.3.2.1 Foam tank vent and overflow system. The foam tank will incorporate a vent system to relieve pressure on the tank during fill and discharge operations at maximum flow rates and an overflow system to relieve excess liquid in the event of tank overflow. Drainage from the vent and overflow system will not be in front of or behind any of the tires. Tank vent hoses will be of the non-collapsible type.

3.6.3.3 Foam transfer pump. A foam transfer pump will be provided and mounted in a compartment on the vehicle. The pump will be capable of transferring and drawing foam liquid concentrate at adjustable flow rates up to 25-gpm directly through the pump and loading connections (see 3.6.3.2). All materials and components that come in contact with the foam will be compatible with the foam concentrate. The pump and its plumbing will have provisions for flushing with water from the water tank. A suitable length of hose with appropriate connections will be provided for filling the foam tank from an external foam storage container.

3.6.3.4 Foam flushing system. The foam concentrate system will be designed in accordance with NFPA 414 so that the system can be readily flushed with clear water.

3.6.3.5 Foam concentrate piping. All metallic surfaces of the piping and associated components that come into contact with the foam concentrate will be of brass, bronze, or passivated stainless steel. The foam concentrate piping will be in accordance with NFPA 414.

3.6.4 Foam proportioning system. The vehicle will have a foam proportioning system for Aqueous Film-Forming Foam (AFFF) (whether 3- or 6-percent foam concentrate) in accordance with NFPA 414. If a fixed orifice plate system is used, a plate will be provided for each percentage foam concentrate; the additional plate will be securely mounted in a protected location on the vehicle. A fire vehicle mechanic will be able to interchange the plates using common hand tools.

3.6.5 Primary vehicle turret. The vehicle will be equipped with a standard roof-mounted turret, high reach extendable turret, and/or high flow bumper mounted turret to serve as the primary source of agent delivery, as specified below:

#### CLASS 4

**3.6.5.1**      Roof turret. The roof turret will be mounted near the front of the roof of the vehicle. It will have a non-air-aspirating, constant flow, variable stream nozzle with dual flow rates for foam or water rated as specified in NFPA 414. The discharge pattern will be infinitely variable from straight stream to fully dispersed. The roof turret will be power operated; power controls will be positioned for use by the driver and the crew member seated to the right of the driver. The type of nozzle or turret drain will be per the manufacturer's recommendation.

**3.6.6**              Bumper turret. The vehicle will be equipped with a joystick controlled, constant flow, non-air-aspirating, variable stream type:

Low angle high volume dual rate (minimum 375/750 GPM) bumper turret.

The bumper turret will be capable of discharging at a minimum flow rates of foam or water as specified by the user, with a pattern infinitely variable from straight stream to fully dispersed. The bumper turret will be capable of automatic oscillation, with the range of oscillation adjustable up to 90° each side of center (left and right) with vertical travel capabilities of +45° / -20° meeting section 4.20.2 in NFPA 414.

**3.6.7**              Preconnected handline(s). **Two** 200 foot, 1 ¾ inch pre-connected woven jacket handline(s), with a 1 ½ inch control valve and a pistol grip nozzle, will be located on (or accessible from) each side of the vehicle. A safety system will be provided to prevent charging of the hose until the hose has been fully deployed. The handline(s) and nozzle(s) will be in accordance with NFPA 414, and will allow for a minimum of 95 GPM at 100 psi nozzle pressure. A control for charging each handline will be provided for operation by both the driver and the turret operator.

**3.6.7.1**              In addition, the vehicle will be equipped with the following handline: 100 feet of twinned 1-inch dry chemical/foam-water hose on a reel.

**3.6.8**              Structural firefighting capability. The vehicle will be equipped with an agent system structural control panel, on the left side of the vehicle, operable while standing on the ground. Structural panel activation will be interlocked to operate only with the vehicle parking brakes set and the transmission in neutral position. Controls and instruments will be grouped by function. The control panel will be hinged or accessible from the rear for maintenance. Instruments will be lighted for night operation.

**3.6.8.1**              The structural panel will include, as a minimum, the following:

- a. Panel activation switch, including the panel lights.
- b. Engine Tachometer.
- c. Engine oil pressure gauge with low pressure warning light.
- d. Engine coolant temperature gauge with high temperature warning light.
- e. A liquid filled gauge, or digital indicator for pump suction. -30 inches Hg vacuum to 600 psi.

- f. A liquid filled gauge, or digital indicator for pump pressure, 0 to 600 psi.
- g. An adjustable pump pressure using either an electronic pressure governor or manual control with a relief valve will be provided.
- h. Foam or water selection.
- i. Water and foam tank liquid level indicators, located adjacent to the water and foam tank fills.

3.6.8.2 The structural fire fighting capability will also require installation of the following items:

- a. A priming pump and control (for drafting using the large intake connection).
- b. Water tank isolation valve.
- c. Discharge connections. Two 2 ½-inch discharge connections with male National Hose threads will be provided. One 2 ½-inch discharge will be provided on each side of the vehicle. Each connection will be equipped with a cap, a quarter-turn control valve, a bleeder valve, and each connection will be equipped with a cap, a quarter-turn control valve, a bleeder valve, and a pressure gauge. Each connection will be rated at 250-gpm minimum.
- d. Intake connections. The vehicle will be equipped with one valved 4 ½-inch intake connection on the left side. The vehicle will be equipped with one valved 2 ½-inch intake connection on the left side. The vehicle will be equipped with one valved 2 ½-inch intake connection on the left side adjacent to the 4 ½-inch intake connection with both having either a 30° or 45° turn-down fitting. The 4 ½-inch intake connection will have male National Hose threads, a quarter turn control valve, a bleeder valve, a strainer, and a cap. The 2 ½-inch intake connection will have rocker lug female National Hose threads, a quarter-turn control valve, a bleeder valve, a strainer, and a plug. The vehicle will be capable of filling its water tank by pumping from a draft, a hydrant, or a nurse truck through either of the intake connections without the use of a hose from a discharge connection to a tank fill connection.

3.6.9 Primary turret discharge nozzle. The vehicle will be equipped with a combination dry chemical/ AFFF nozzle of the entrainment type on the primary turret mounted on the cab roof.

#### CLASS 4

3.7 Dry chemical agent system. The vehicle will be equipped with a 450 lb minimum capacity potassium bicarbonate based dry chemical agent system. The propellant gas cylinder will be replaceable within fifteen minutes by two crew members standing on the ground and be equipped with a cylinder replacement hoisting system. The propellant gas cylinder will be secured to withstand off-road operations. A pressure indicator will be visible to any person opening the tank fill cap. Blow-down piping will be directed beneath the vehicle. The dry chemical agent tank will include lifting rings and will have a nameplate indicating, as a minimum, the following:

- a. Extinguishing agent.
- b. Capacity.
- c. Weight full.
- d. Weight empty.
- e. Operating pressure.
- f. Hydrostatic test date.
- g. Type of agent required for re-servicing.

3.7.1 Not applicable.

3.7.2 Dry chemical hose reel. A hose reel, equipped with at least 100 feet of dry chemical hose, will be mounted in a compartment. Handline agent and purge controls will be mounted in or adjacent to the compartment. All electrical components will be sealed against entry of water. The hose reel will have both electric and manual rewind provisions. The manual rewind handle will be bracket mounted and stored in the compartment. A quick acting control will be provided to activate the handline from the cab of the vehicle.

3.8 Not applicable.

3.9 Electrical systems and warning devices. The vehicle will have a 12-volt or 24-volt electrical and starting system in accordance with NFPA 414.

3.9.1 Alternator. An appropriate charging system, in accordance with NFPA 414, will be provided. The minimum continuous electrical load will include operation of the air conditioning system.

#### CLASS 4

3.9.2 Batteries. Batteries will be of the maintenance-free type; addition of water will not be required during normal service life. The battery cover and vent system will be designed to prevent electrolyte loss during service and to keep the top of the battery free from electrolyte.

3.9.2.1 Battery compartment. The batteries will be enclosed in a weatherproof enclosure, cover, or compartment and be readily accessible.

3.9.3 Battery charger or conditioner. The vehicle will have a DC taper type batter charger or an automatic battery conditioner, or voltage monitoring system, providing a minimum 12 amp output. The charger/conditioner will be permanently mounted on the vehicle in a properly ventilated, accessible location. The charger/conditioner will be powered from the electrical shoreline receptacle (see 3.10.1). A charging indicator will be installed next to the receptacle. When a battery conditioner is provided, the conditioner will monitor the battery state of charge and, as necessary, automatically charge or maintain the batteries without gassing, depleting fluid level, overheating, or overcharging. A slave receptacle will be provided at the rear or on either side of the vehicle cab. Battery jump studs may be installed on the exterior of the battery box in lieu of a slave receptacle.

3.9.4 Electromagnetic interference. The vehicle electrical system will be in accordance with SAE J551-2 for electromagnetic interference.

3.9.5 Work lighting.

3.9.5.1 Cab interior lights. Cab interior light levels will be sufficient for reading maps or manuals. At least one red and one white cab interior dome light will be provided.

3.9.5.2 Compartment lights. White lighting sufficient to provide an average minimum illumination of 1.0 foot-candle will be provided in each compartment greater than 4.0 cubic feet and having an opening greater than 144 square inches. Where a shelf is provided, this illumination will be provided both above and below the shelf. All compartments will be provided with weatherproof lights that are switched to automatically illuminate when compartment doors are opened and the vehicle master switch is in the 'on' position. Light switches will be of the magnetic (non-mechanical) type.

3.9.5.3 Ladder, step, walkway, and area lights. Non-glare white or amber lighting will be provided at ladders and access steps where personnel work or climb during night operations. In addition, ground lighting will be provided. Ground lights will be activated when the parking brake is set in accordance with AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. These area lights will be controlled with three-way switches on the cab instrument panel and near the light source. The switch located in the cab will be a master switch and must be turned on before auxiliary switches near the light sources are operational.

3.9.5.4 Spot/Floodlights. Two spot/floodlights will be attached at the end of the primary turret or at the end of the HRET assembly. The lights will illuminate the area covered by the turret. Both lights will be controlled from switches in the cab. LED lights will be used.

3.9.5.5 Flood lights. Two telescoping floodlights will be provided. One light will be mounted on the left and right sides of the vehicle. 250 W LED lights will be used.

Both lights will be mounted on extension tubes and controlled from switches in the cab and manually raised. To prevent these lights from accidental damage, the cab will be equipped with a visual warning signal to alert the driver if the lights are inadvertently left in the "up" position.

3.9.5.6 Scene lights. A total of six high mounted floodlights will be provided to illuminate the work areas around the vehicle. Two lights will be mounted on the front and two will be mounted on each side of the vehicle. The lights will be powered by the vehicle alternator driven system or auxiliary generator, and the lights in the front will be controlled from switches in the cab. **LED** lights will be used.

3.9.6 Audible warning devices.

3.9.6.1 Siren. The vehicle will be equipped with an electronic siren system. The amplifier unit will include volume control and selection of "Radio", "PA", "Manual", "Yelp", "Wail", and "Hi-Lo" (European) modes, and a magnetic noise canceling microphone. The amplifier, microphone, and controls will be within reach of the driver and the turret operator. Siren activating foot switches will be located in front of the driver and the turret operator. The siren speaker will be rated at 100 watts minimum and will be located in a guarded position as low and as far forward on the vehicle as practical.

3.9.6.2 Horn. Dual forward-facing air horns will be installed in protected locations near the front of the vehicle. Air horn activating foot switches will be located in front of the driver and the turret operator.

3.9.7 Emergency warning lights. All emergency warning lights must meet the requirements of AC 150/5210-5. Where applicable **LED** lights will be used as the primary light type. Lighting units will be installed on the top front, sides, and rear of the vehicle to provide 360° visibility. A switch will be provided on the instrument panel to control all of the top, side, front and rear emergency warning lights. A switch will also be provided on the instrument panel to disable all lower emergency warning lights when desired. All lighting systems will meet NFPA 414 emergency lighting criteria.

3.9.7.1 Emergency warning light color. All emergency warning lights will meet the requirements of AC 150/5210-5.

3.9.7.2 Headlight flashing system. A high beam, alternating/flashing, headlight system will be provided. The headlight flasher will be separately switched from the warning light panel. All emergency warning lights will meet the requirements of AC 150/5210-5.

3.9.8 Radio circuit. The vehicle will have three separate 30-amp circuits with breakers and connections provided in a space adjacent to the driver and turret operator for installation of radios and other communications equipment after the vehicle has been delivered. To facilitate the installation of the communications equipment the manufacturer will provide three antennas pre-installed on top of the cab. **Radios are an airport responsibility and not part of this specification.**

3.9.9 Power receptacles.

3.9.9.1 Primary power receptacles. The vehicle will have two duplex 15-amp 110-volt power receptacles, one installed adjacent to the cab door on each side of the vehicle. Each duplex receptacle will include one straight blade and one twist-lock connection. These outlets will be powered by the generator.

3.9.9.2 Auxiliary power receptacles. The vehicle will have 2-12-volt auxiliary power receptacles mounted adjacent to the driver and crew member positions, preferably in the instrument panel.

3.9.9.3 Cable reel. The vehicle will be equipped with an electrical reel, located within a compartment. The reel will be equipped with 200 feet of 20 amp, 600 volt, 90°C insulated electrical cable. The electrical cable will be equipped with a rubber ball stop to prevent cable pull through during rewinding operations. A four-way roller guide will be provided on the cable reel to prevent chafing of cable insulation. The cable reel will have an electric rewind motor with provisions for manual rewind in the event of motor failure; the manual rewind handle will be securely stored near the cable reel. A portable weatherproof duplex outlet box, with built-in circuit breakers and twist-lock receptacles, will be provided for on the cable end. The cable reel will be powered by the auxiliary generator.

3.9.10 Auxiliary generator. A minimum **10** kilowatt (kW) (continuous rating), 120/240-volt, 60 hertz, diesel, hydraulic, or split shaft Power Takeoff (PTO)-driven generator will be provided.

3.10 Line voltage electrical system.

3.10.1 Electrical shoreline connection. The battery charger/conditioner will be powered from a covered, polarized, insulated, labeled, recessed (flush mounted), male, 110-volt AC auto-eject receptacle. The connection will be located on the exterior of the vehicle at the rear or on either side of the cab. A weatherproof charge meter will be installed next to the receptacle. A 15-amp rated, 110-12-volt, AC straight blade (non-twist-lock) connector will be provided.

3.11 Air systems.

3.11.1 Air hose reel. An air hose reel will be provided in an enclosed compartment on the vehicle. The hose reel will be equipped with 200 feet of 3/8-inch I.D. hoseline. A 3/8-inch National Pipe Taper (NPT) fitting and female style quick disconnect will be connected to the end of the hoseline. A four-way roller guide will be provided for the hose reel to prevent hose chafing and kinking. The hoseline will be equipped with a rubber ball stop to prevent hose pull through on roller guides during rewinding operations. The hose reel will have an electric rewind motor and provisions for manual rewind in the event of motor failure; the manual rewind handle will be securely stored near the hose reel. A pressure protected air supply from the chassis air system will be connected to the hose reel. The air supply lines will be routed with minimum bends and located or guarded from damage from the carried equipment.

3.12 Quality of Workmanship. The vehicle, including all parts and accessories, will be fabricated in a thorough workmanlike manner. Particular attention will be given to freedom from blemishes, burrs, defects, and sharp edges; accuracy of dimensions, radii of fillets, and marking of parts and assemblies; thoroughness of welding, brazing, soldering, riveting, and painting; alignment of parts; tightness of fasteners; et cetera. The vehicle will be thoroughly cleaned of all foreign matter.

#### CLASS 4

#### 4. REGULATORY REQUIREMENTS

4.1 Recoverable Materials. The contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with Title 48: Federal Acquisition Regulations System, Part 2823-Environment, Conservation, Occupational Safety, and Drug-Free Workplace, Subpart 2823.4 Use of Recovered Material, 403 Policy and 404 Procedures.

4.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchases that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired:

- a. competitively within a reasonable timeframe;
- b. meet appropriate performance standards, or
- c. at a reasonable price.

The prime contractor is responsible for ensuring that all subcontractors comply with this requirement. Information on the GPP can be found at:

[http://www.dot.gov/ost/m60/DOT\\_policy\\_letters/apl8\\_04.pdf](http://www.dot.gov/ost/m60/DOT_policy_letters/apl8_04.pdf) or FAR 23.404(b):  
<http://www.acquisition.gov/far/current/html/Subpart%2023.4.html>.

#### 5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

- a. Performance inspection (see 5.2).
- b. Conformance inspection (see 5.3).

5.2 Performance inspection. The vehicle will be subjected to the examinations and tests described in 5.6.3.5 (if applicable). The contractor will provide or arrange for all test equipment, personnel, schedule, and facilities.

5.3 Conformance inspection. The vehicle will be subjected to the examinations and tests described in 5.6.3.1 through 5.6.3.5 (if applicable). The contractor will provide or arrange for all test equipment, personnel, and facilities.

5.4 Product conformance. The products provided will meet the performance characteristics of this PS, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The purchaser reserves the right to require proof of such conformance.

5.5 Technical proposal. The offeror/contractor will provide an itemized technical proposal that describes how the proposed model complies with each characteristic of this PS; a paragraph by paragraph response to the characteristics section of this PS will be provided. The offeror/contractor will

provide two copies of their commercial descriptive catalogs with their offer as supporting reference to the itemized technical proposal. The offeror/contractor will identify all modifications made to their commercial model in order to comply with the requirements herein. The vehicle furnished will comply with the "commercial item" definition of FAR 2.101 as of the date of award. The purchaser reserves the right to require the offeror/contractor to prove that their product complies with the referenced commerciality requirements and each conformance/performance characteristics of this PS.

5.6 Inspection requirements.

5.6.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein will be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

5.6.2 Test rejection criteria. Throughout all tests specified herein, the vehicle will be closely observed for the following conditions, which will be cause for rejection:

- a. Failure to conform to design or performance requirements specified herein or in the contractor's technical proposal.
- b. Any spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid, under any condition, except as allowed herein.
- c. Structural failure of any component, including permanent deformation, or evidence of impending failure.
- d. Evidence of excessive wear.
- e. Interference between the vehicle components or between the vehicle, the ground, and all required obstacles, with the exception of normal contact by the tires.
- f. Misalignment of components.
- g. Evidence of undesirable road ability characteristics, including instability in handling during cornering, braking, and while traversing all required terrain.
- h. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.
- i. Overheating of the engine, transmission, or any other vehicle component.
- j. Evidence of corrosion.
- k. Failure of the firefighting system and sub-systems.

5.6.3 Detailed inspection requirements.

5.6.3.1 Examination of product. All component manufacturers' certifications, as well as the prototype and production/operational vehicle testing outlined in Table 1, will be examined to verify compliance with the requirements herein. Attention will be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of vehicle functions will be verified as defined by NFPA 414, Acceptance

Criteria chapter. A copy of the vehicle manufacturer's certifications will be provided with each vehicle in accordance with NFPA 414. The airport may accept a manufacturer or third-party certification for any/all prototype and production/operational vehicle testing performed prior to delivery which proves that the vehicle meets the performance parameters of NFPA 414.

**Table 1. Vehicle Test Data**

<b>NFPA 414 Paragraph</b>	<b>Test</b>
<b>Production Vehicle Operational Test (NFPA 414 – Section 6.4)</b>	
(6.4.1)	Vehicle Testing, Side Slope
(6.4.2)	Weight/Weight Distribution
(6.4.3)	Acceleration. <b>NOTE:</b> <i>With the modification that the instrumentation must be a GPS-based electronic data collection system.</i>
(6.4.4)	Top Speed
(6.4.5)	Brake Operational Test
(6.4.6)	Air System / Air Compressor Test
(6.4.7)	Agent Discharge Pumping Test
(6.4.8)	Dual Pumping System Test (As Applicable)
(6.4.9)	Pump and Maneuver Test
(6.4.10)	Hydrostatic Pressure Test
(6.4.11)	Foam Concentrate Test
(6.4.12)	Primary Turret Flow Rate Test
(6.4.13)	Piercing/Penetration Nozzle Testing (As Applicable)
<b>Prototype Vehicle Test (NFPA 414-Section 6.3)</b>	
(6.3.1)	Rated Water and Foam Tank Capacity Test
(6.3.2)	Cornering Stability. <b>NOTE:</b> <i>With the modification that the evasive maneuver / double-lane change test must be conducted at 35 mph (56 kph).</i>
(6.3.3)	Vehicle Dimensions
(6.3.4)	Driver Vision Measurement
(6.3.5)	Pump and Roll on a 40 Percent Grade
(6.3.6)	Electrical Charging System
(6.3.7)	Radio Suppression
(6.3.8)	Gradability Test
(6.3.9)	Body and Chassis Flexibility Test
(6.3.10)	Service/Emergency Brake Test
(6.3.11)	Service/Emergency Brake Grade Holding Test
(6.3.12)	Steering Control Test
(6.3.13)	Vehicle Clearance Circle Test
(6.3.14)	Agent Pump(s)/Tank Vent Discharge Test
(6.3.15)	Water Tank Fill and Overflow Test
(6.3.16)	Flushing System Test
(6.3.17)	Primary Turret Flow Rate Test
(6.3.18)	Primary Turret Pattern Test
(6.3.19)	Primary Turret Control Force Measurement
(6.3.20)	Primary Turret Articulation Test
(6.3.21)	Handline Nozzle Flow Rate Test

(6.3.22)	Handline Nozzle Pattern Test
(6.3.23)	Ground Sweep/Bumper Turret Flow Rate
(6.3.24)	Ground Sweep/Bumper Turret Pattern Control Test
(6.3.25)	Undertruck Nozzle Test
(6.3.26)	Foam Concentration/Foam Quality Test
(6.3.27)	Warning Siren Test
(6.3.28)	Propellant Gas
(6.3.29)	Pressure Regulation
(6.3.30)	AFFF Premix Piping and Valves
(6.3.31)	Pressurized Agent Purging and Venting
(6.3.32)	Complementary Agent Handline Flow Rate and Range
(6.3.33)	Dry Chemical Turret Flow Rate and Range
(6.3.34)	Cab Interior Noise Test

#### 6. Packaging.

6.1 Preservation, packing, and marking will be as specified in the Procurement Specification, contract or delivery order.

6.2 The Vehicle must be delivered with full operational quantities of lubricants, brake and hydraulic fluids, and cooling system fluid all of which must be suitable for use in the temperature range expected at the airport.

6.3 The vehicle must be delivered with one complete load of firefighting agents and propellants. One complete load is defined as all of the agents and propellants necessary for the vehicle to be fully operational. One load would include, at a minimum: one fill of a foam tank; one fill of a dry chemical tank (if applicable); one fill of a halogenated tank (if applicable); one spare nitrogen cylinder for a dry chemical system (if applicable); and one spare argon cylinder for a halogenated system (if applicable). Agents and propellants for required testing or training are not included. For the initial training period, water should be used in place of other extinguishing agents. The manufacturer may pre-ship agents and propellants to a receiving airport to reduce overall procurement costs.

6.4 The vehicle manufacturer must provide initial adjustments to the vehicle for operational readiness and mount any ancillary appliances purchased through the vehicle manufacturer as part of the vehicle.

#### 7. TRAINING.

7.1 Upon delivery of the vehicle to the airport, the manufacturer must, at no additional cost, provide the services of a qualified technician for five consecutive days for training. This is considered sufficient time for the purchaser to adjust shift work schedules to get maximum employee attendance to training sessions at some point during the training period. During this time sufficient repetitive learning opportunities must be provided by the manufacturer to allow various shifts to complete the training requirements.

7.2 The technician must provide thorough instruction in the use, operation, maintenance and testing of the vehicle. This setup must include operator training for the primary operators, which will give them sufficient knowledge to train other personnel in the functional use of all fire fighting and vehicle operating systems. Prior to leaving the vehicle, the technician should review the maintenance instructions with the purchaser's personnel to acquaint them with maintenance procedures as well as how to obtain support services for the vehicle.

7.3 Training must include written operating instructions, electronic training aids (video/power point), or other graphics that depict the step-by-step operation of the vehicle. Written instructions must include materials that can be used to train subsequent new operators.

8. REFERENCE DOCUMENTS.

8.1 Source of documents.

8.1.1 The CFR may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington DC 20402.

Title 14, Code of Federal Regulations (CFR), Part 139, Certification of Airports (14 CFR Part 139)

Section 139.315 Aircraft Rescue and Firefighting: Index Determination.

Section 139.317 Aircraft Rescue and Firefighting: Equipment and Agents.

Section 139.319 Aircraft Rescue and Firefighting: Operational Requirements.

Title 49; Code of Federal Regulations (CFR), Part 393: Parts and Accessories Necessary for Safe Operation: Subpart C – Brakes.

Title 49; Code of Federal Regulations (CFR), Part 571, Motor Carrier Vehicle Safety Standards, Part 209, Standard No. 209; Seat Belt Assemblies.

8.1.2 SAE documents may be obtained from SAE, Inc., 400 Commonwealth Drive, Warrendale PA 15096.

8.1.3 National Fire Protection Association (NFPA): NFPA documents may be obtained from NFPA, Batterymarch Park, Quincy MA 02269-9101.

NFPA 412, Standard for Evaluating Aircraft Rescue and Fire Fighting Foam Equipment (2009 Edition)

NFPA 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition)

NFPA 1901, Standard for Automotive Fire Apparatus (2009 Edition)

8.1.4 Federal Aviation Administration (FAA): FAA ACs may be obtained from the FAA website: [http://www.faa.gov/regulations\\_policies/advisory\\_circulars/](http://www.faa.gov/regulations_policies/advisory_circulars/).

AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles

AC 150/5210-5, Painting, Marking, and Lighting of Vehicles Used on an Airport

**CLASS 4**

FAA Orders, Specifications, and Drawings may be obtained from: Federal Aviation Administration, ATO-W CM-NAS Documentation, Control Center, 800 Independence Avenue, SW, Washington, DC 20591.

Telephone: (202) 548-5256, FAX: (202) 548-5501 and website:

[http://www.faa.gov/about/office\\_org/headquarters\\_offices/ato/service\\_units/techops/atc\\_facilities/cm/cm\\_documentation/](http://www.faa.gov/about/office_org/headquarters_offices/ato/service_units/techops/atc_facilities/cm/cm_documentation/)

To: Northwest Florida Beaches International Airport  
6300 West Bay Parkway  
Box A  
Panama City, FL 32409

Date: May 7, 2021

We hereby propose and agree to furnish, after your acceptance of this proposal and the proper execution by the Northwest Florida Beaches International Airport, hereinafter called the Buyer and an officer of Rosenbauer Minnesota, LLC, hereinafter called the Company, the following apparatus and equipment.

One (1) Rosenbauer Panther 4x4 Apparatus Body	\$689,820.00
Gross due upon completion and delivery Total	\$689,820.00*

Six Hundred Eighty Nine Thousand Eight Hundred Twenty Dollars\*  
\*\*DOES NOT INCLUDE TAX, BID VALID FOR 90 DAYS\*\*

All of which are to be built in accordance with the specifications, clarifications and exceptions attached, and which are made a part of this agreement and contract.

**DELIVERY:** The estimated delivery time for the completed apparatus, is to be made 395 days after receipt of and approval of this contract duly executed, (chassis and (or) major components must arrive within 150 days or delivery may be extended), subject to all causes beyond the Company's control. The quoted delivery time is based upon our receipt of the approved specifications within 60 days of contract signing. "Delivery" means the date company is prepared to make physical possession of vehicle available to the customer.

**CONTRACT CHANGES:** After execution and acceptance of this Contract, the Buyer may request that the Company incorporate a change to the Products or the Specifications for the Products by delivering a Change Order to the Company; provided, however, that any such Change Order must be in writing and include a description of the proposed change sufficient to permit the Company to evaluate the feasibility of such Change Order. Within seven (7) working days of receipt of a Change Order, the Company will inform the Buyer in writing of the feasibility of the Change Order, the earliest possible implementation date for the Change Order, of any increase or decrease in the Purchase Price resulting from such Change Order, and of any effect on production scheduling or delivery resulting from such Change Order. The Company shall not be liable to the Buyer for any delay in performance or delivery arising from any such Change Order. Purchase Price may be modified only by mutual written agreement of the Parties because of changes to the Apparatus required or requested by the Buyer during the construction process pursuant to Appendix C, Change Order Policy. Any changes in the Purchase Price resulting from changes to the Apparatus required or requested by the Buyer during the construction process shall be stated in the Change Order signed by both parties. Additional Changes: If various state or federal regulatory agencies (e.g. NFPA, DOT, EPA) require changes to the specification and/or the product that result in a cost increase to comply therewith this cost will be added to the Purchase Price to be paid by the customer.

**FORCE MAJEURE:** The Company shall not be responsible nor deemed to be in default on account of delays in performance due to causes which are beyond the Company's control which make the Company's performance impracticable, including but not limited to civil wars, insurrections, strikes, riots, fires, storms, floods, other acts of nature, explosions, earthquakes, accidents, any act of government, delays in transportation, inability to obtain necessary labor supplies or manufacturing facilities, allocation regulations or orders affecting materials, equipment, facilities or completed products, failure to obtain any required license or certificates, acts of God or the public enemy or terrorism, failure of transportation, epidemics, quarantine restrictions, failure of vendors (due to causes similar to those within the scope of this clause) to perform their contracts or labor troubles causing cessation, slowdown, or interruption of work.

**PAYMENT TERMS:** Final payment for the apparatus shall be made at time of delivery or pick up of the completed vehicle. It is the responsibility of the Buyer to have full payment ready when the apparatus is complete and ready to deliver. If payment is delayed or delivery is delayed pending payment, a daily finance and storage fee may apply. Upon delivery of the apparatus or upon pickup of the apparatus by the Buyer, the Buyer agrees to provide all liability and physical damage insurance. It is further agreed that if on delivery and testing, any defects should develop, the Company shall be given reasonable time to correct changes. Guarantee of the chassis is subject to the guarantee of the chassis manufacturer. \*NOTE: upon final inspection at the factory for pick-up or delivery, the Buyer will need to supply a Certificate of Insurance and full payment prior to release of the vehicle, unless prior arrangements for vehicle's release have been made.

**TITLE:** The Apparatus shall always be the property of the Company until it is delivered to the Buyer pursuant to the terms of this agreement. The Company shall bear the sole responsibility and risk for destruction, loss or damage to the apparatus, or any portion of the Apparatus, through the date and time it is delivered to the Buyer. The Company shall deliver good and merchantable title to the Apparatus at the time it is delivered to the Buyer. The Buyer shall bear the sole responsibility and risk for destruction, loss or damage to the Apparatus upon the date and time it takes delivery of the Apparatus.

[www.rosenbaueramerica.com](http://www.rosenbaueramerica.com)

[info@rosenbaueramerica.com](mailto:info@rosenbaueramerica.com)

ROSENBAUER SOUTH DAKOTA, LLC.  
100 THIRD STREET  
P.O. BOX 57  
LYONS, SOUTH DAKOTA 57041  
P: 605.543.5591

ROSENBAUER MINNESOTA, LLC.  
5181 260TH STREET  
P.O. BOX 549  
WYOMING, MINNESOTA 55092  
P: 651.462.1000

ROSENBAUER MOTORS, LLC.  
5190 260TH STREET  
P.O. BOX 549  
WYOMING, MINNESOTA 55092  
P: 651.462.1000

ROSENBAUER AERIALS, LLC.  
870 SOUTH BROAD STREET  
FREMONT, NEBRASKA 68025  
P: 402.721.7622



**PIGGY BACK ORDERS:** The Company, at its sole discretion, will allow the terms of the contract to be extended to both the Buyer, as well as to other Municipal, State, or Federal agencies for similar unit(s). The Company will allow tag on / additional orders for up to three (3) years from the date of contract execution. To facilitate pricing, the Company will quote the original price plus manufacturer's price increases or Producer's Price Index (PPI) whichever is greater as it applies to either Fire Apparatus and/ or commercial heavy truck industries.

**MISCELLANEOUS PROVISIONS:** This agreement shall be construed in accordance with the laws of the State of Minnesota. The parties agree that any litigation arising from or in connection with any dispute between the parties under this agreement shall be venue in Minnesota. The parties agree that this agreement bears a rational relationship to the State of Minnesota, and they consent to the personal jurisdiction of such state and further consent and stipulate to venue in the above-described court.

Respectfully submitted,

**DEALER:** DUANE KANN

**BUYER:**

We accept the above proposal and  
enter into contract with signature below.

\_\_\_\_\_ Title \_\_\_\_\_

\_\_\_\_\_ Title \_\_\_\_\_

\_\_\_\_\_ Date \_\_\_\_\_

*After company receipt of this document signed by the Buyer, the document will be reviewed and upon approval, countersigned by the Company thereby putting the document in force.*

**ROSENBAUER MINNESOTA, LLC**

Christian Kleebauer - CEO

Date: 5/7/2021

[www.rosenbaueramerica.com](http://www.rosenbaueramerica.com)

[info@rosenbaueramerica.com](mailto:info@rosenbaueramerica.com)

ROSENBAUER SOUTH DAKOTA, LLC.  
100 THIRD STREET  
P.O. BOX 57  
LYONS, SOUTH DAKOTA 57041  
P: 605.543.5591

ROSENBAUER MINNESOTA, LLC.  
5181 280TH STREET  
P.O. BOX 549  
WYOMING, MINNESOTA 55092  
P: 651.462.1000

ROSENBAUER MOTORS, LLC.  
5190 280TH STREET  
P.O. BOX 549  
WYOMING, MINNESOTA 55092  
P: 651.462.1000

ROSENBAUER AERIALS, LLC.  
870 SOUTH BROAD STREET  
FREMONT, NEBRASKA 68025  
P: 402.721.7622